

Client:
MTS

Project:
1297287
BROCK ROAD,
GREAT ECCLESTON,
PRESTON PR3 0XE

Title:
Road Closure

DESIGN INPUTS	
D1	☐
D2	☐
D3	☒
D4	☐
D5	☒
D10	☒

(FOR REFERENCE RELATE TO CONTROL DOCUMENT: F-012-DesignRefs (iss 1))

D10 - OTHER? PLEASE STATE:

Job Request email, Attached job notes & MTS Optimus System

Key:	
	Traffic sign
	Traffic cone/cylinder
	Traffic signals to Diagram 3000.1
	Pedestrian barrier
	Stop/Go board (P7023/P7024)
	Work Area
	Area of road closed
	Diversion Route
	Temporary vehicle restraint barrier

This Drawing is the property of
Dutton Traffic Management Services.

It MUST NOT be copied in part or sent to
a third party without written permission.

DETAIL B (B)
Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m. Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m. Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.
Notes: 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1). 2) 45° tapers have 1.5m spacing, no relaxations. 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1 (C1)
Single/Dual carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.
Notes: 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1). 2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Drawn:	Checked:
Lee Bellfield	Gary Mainwaring

01/08/2025	Rev: 1
------------	--------

DT34952-01-01
Original drawing size A3 - NTS

